

MASI600

Airborne Hyperspectral MWIR Imager (3-5 microns)

64 Spectral Channels

40° FOV, 600 Spatial Imaging Pixels

Internally Cooled Array - High SNR with Electronic Noise Suppression

Custom diffraction-limited, high-performance optics¹



HYPER SPECTRAL & THERMAL REMOTE SENSING

¹Diffraction-limited optics ensure that every pixel is a spatially independent sample with no smearing. This gives users optimal image quality and focus.

MASI600

Biochemical Gas Detection / Invasive Species / Surface Landmine Detection / Unexploded Ordnance / Pipeline Leakage / Mineral Composition / Structural Geology / Oil Slick Mapping

SENSOR TYPE

MWIR Pushbroom Sensor
(Midwave IR Airborne Spectrographic Imager)

PERFORMANCE

Spectral Range (Continuous Coverage)	3.0-5.0 microns
# Spectral Channels	64
# Spatial Pixels	600
Total Field of View	40 degrees
IFOV (+/- 10%)	1.2 mRad
f/#	f/2.0
Spectral Resolution (FWHM)	32 nm (approx)
Dynamic Range	14-bits (16384:1)
Sustained Data Rate, Mpix/Second	2.4 Mpix/Sec
Spectral Smile/ Keystone Distortion	v±0.33 pixels
Peak Signal to Noise Ratio	SNR models for various radiance conditions are available.

MASI-600 Imagery:



DIMENSIONS, WEIGHTS, AND POWER

ITEM	W / H / D (CM) / WT. (KG)
SHU	TBD
ICU	48.3 / 17.8 / 52.3 / 16
15" Display	41.0 / 30.9 / 6.52 / 8
Power	24-32VDC 15A (Typical - est.)

ENVIRONMENTAL CONSTRAINTS

Operating Temperature	Ambient 0 to +35°C (+32 to +104°F) RH 20-80% non-condensing
Maximum Altitude	3,048m (10,000 ft) ASL (unpressurized, non-condensing environment)
Storage Temperature	Optimum -20 to +60°C (-4 to +120°F) RH 10-90% non-condensing

OPERATION

Display	5" sunlight readable, 1024x768 resolution. High altitude display available.
Operator Control	Via keyboard, Windows™ OS
Real-Time Display	Scene Image, automated sensor health diagnostics, signal level display
Remote Diagnostics	Ethernet-ready remote diagnostic capability on ICU
Data Storage	Swappable mass storage
Multiple Sensor Operation	Up to 5 ITRES imagers may be simultaneously operated via MuSIC™ System

DATA PROCESSING SYSTEM

- Processing software Linux and Windows-based
- Playback software (Quicklook)
- Generates 16-bit BIP format data compatible with ENVI (BIL, BSQ formats possible)
- ASCII format ancillary QC data output – clocking, attitude, logging, GPS, and sensor health monitoring information
- Outputs diagnostic information
- Selectable band output

GEOCORRECTION SYSTEM

- GPS/IMU integration to POS AV (other systems available)
- Data synchronization (GPS, attitude, and image streams)
- Precision positional accuracy
- After bundle adjustment no need for GCPs
- Stabilized mount option

GEOCORRECTION/ORTHO CORRECTION/MOSAICKING SOFTWARE


- Best nadir pixel selection function during mosaicking
- Accepts Lidar, Ifsar, and USGS DEM inputs
- Nearest neighbor algorithm used – maintains radiometric fidelity
- Separately stores ancillary data (e.g. pointing vector, DEM)

HOURLY COVERAGE (35% SIDELAP)

- Over 70 km² at one meter spatial resolution

SPATIAL RESOLUTION & FLIGHT ALTITUDE

- Resolutions between 1 m to 3.5 m possible with typical unpressurized aircraft at 110 knots
- 1m Pixel Example: Flight altitude = 2704 ft AGL, Air speed = 110 knots required flight speed is 120 knots



ITRES Research Limited

Calgary, Alberta, Canada
T: +1.403.250.9944
F: +1.403.250.9916

USA Contact Information
T: +1.228.467.2345
TF: +1.877.250.9944

info@itres.com
www.itres.com

Document ID: U10058-03
© 2010 ITRES Research Ltd

All ITRES sensors are calibrated to traceable standards. Specifications subject to change without notice.